

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

1. Identification

- **Product identifier**
- **Trade name:** *WATERPROOF RUBBER SEALANT PASTE*
- **Article number:** *GO602*
- **Application of the substance / the mixture** *Paint*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GoRubber Coatings
Laval, QC Canada H7L 5A1
- **Information department:** *Product safety department*

EMERGENCY PHONE NUMBERS:
USA and Canada: 1-888-226-8832

2. Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapor.
Carc. 1B H350 May cause cancer.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
n-butyl acetate
Distillates (petroleum), hydrotreated middle
- **Hazard statements**
H226 Flammable liquid and vapor.
H350 May cause cancer.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
Keep out of reach from children.

<i>P201</i>	<i>Obtain special instructions before use.</i>
<i>P202</i>	<i>Do not handle until all safety precautions have been read and understood.</i>
<i>P210</i>	<i>Keep away from heat/sparks/open flames/hot surfaces. - No smoking.</i>
<i>P240</i>	<i>Ground/bond container and receiving equipment.</i>
<i>P241</i>	<i>Use explosion-proof electrical/ventilating/lighting/equipment.</i>
<i>P242</i>	<i>Use only non-sparking tools.</i>
<i>P243</i>	<i>Take precautionary measures against static discharge.</i>
<i>P261</i>	<i>Avoid breathing dust/fume/gas/mist/vapors/spray</i>
<i>P271</i>	<i>Use only outdoors or in a well-ventilated area.</i>
<i>P280</i>	<i>Wear protective gloves/protective clothing/eye protection/face protection.</i>

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 1)

- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = *0

Fire = 3

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3. Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

123-86-4	n-butyl acetate	10-30%
540-88-5	tert-butyl acetate	1-5%
64742-46-7	Distillates (petroleum), hydrotreated middle	0.1-1%

4. First-aid measures

· **Description of first aid measures**· **General information:** Immediately remove any clothing soiled by the product.· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** Immediately rinse with water.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 2)

5. Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters** Not available
- **Protective equipment:** No special measures required.

6. Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7. Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8. Exposure controls/personal protection

- **Additional information about design of technical systems:** No information available.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 3)

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m ³ , 200 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

Use splash goggles, solvent resistant gloves. Long-sleeved clothing ideally made of cotton. A cartridge mask.

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 4)

9. Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.

· pH-value:	Not determined.
-------------	-----------------

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	124-128 °C (255.2-262.4 °F)

· Flash point:	27 °C (80.6 °F)
----------------	-----------------

· Flammability (solid, gaseous):	Not applicable.
----------------------------------	-----------------

· Ignition temperature:	370 °C (698 °F)
-------------------------	-----------------

· Decomposition temperature:	Not determined.
------------------------------	-----------------

· Auto igniting:	Product is not selfigniting.
------------------	------------------------------

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
------------------------	--

· Explosion limits:

· Lower:	1.2 Vol %
· Upper:	7.5 Vol %

· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
------------------------------------	--------------------

· Density:	Not determined.
------------	-----------------

· Relative density	Not determined.
--------------------	-----------------

· Vapor density	Not determined.
-----------------	-----------------

· Evaporation rate	Not determined.
--------------------	-----------------

· Solubility in / Miscibility with

· Water:	Not miscible or difficult to mix.
----------	-----------------------------------

· Partition coefficient (n-octanol/water):	Not determined.
--	-----------------

· Viscosity:

· Dynamic:	Not determined.
------------	-----------------

· Kinematic:	Not determined.
--------------	-----------------

· Other information	No further relevant information available.
---------------------	--

10. Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability** The product is stable at room temperature.

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** Keep away from heat

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11. Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** No irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12. Ecological Information

· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.

13. Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 6)

14. Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name · DOT · ADR · IMDG, IATA	Paint 1263 PAINT PAINT
· Transport hazard class(es) · DOT	
	
· Class · Label	3 Flammable liquids 3
· ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids 30 F-E, S-E A
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 7)

· UN "Model Regulation":

UN 1263 PAINT, 3, III

15. Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



- **Signal word** Danger

- **Hazard-determining components of labeling:**

n-butyl acetate

Distillates (petroleum), hydrotreated middle

- **Hazard statements**

H226 Flammable liquid and vapor.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2021

Reviewed on 01/22/2021

Trade name: **WATERPROOF RUBBER SEALANT PASTE**

(Contd. of page 8)

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:** HS REG.DEPART.REG.SS

· **Date of preparation / last revision** 01/22/2021 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3